

AIR OPERATED LOCKING DIFFERENTIAL

RD119

Ford 9",31 SPL

PARTS L	IST			
ITEM#	QTY	DESCRIPTION	PART#	NOTES
01	1	TAPERED ROLLER BEARING	NOT SUPPLIED	
02	1	FLANGE CAP KIT	027306SP	
03	1	SPLINED SIDE GEAR	SEE NOTE	2
04	1	SPIDER BLOCK	070201SP	
05	1	LONG CROSS SHAFT	060204SP	
06	1	SIDE GEAR	SEE NOTE	2
07	1	COUNTERSUNK SCREW (PK OF 2)	200213SP	
08	1	RETAINING PIN SET (PK OF 4)	120701SP	
09	1	TAPERED ROLLER BEARING	NOT SUPPLIED	
10	1	SEAL HOUSING RETAINING CLIP	150602SP	
11	1	SEAL HOUSING KIT	082002SP	
12	1	SEAL HOUSING O-RINGS (PK OF 2)	160235SP	1
13	1	ADJUSTER NUT (75.3mm [2.95"])	100703SP	
*	1	ADJUSTER NUT (80mm [3.15"])	100704SP	
14	1	BONDED SEAL	160703SP	
15	1	CLUTCH GEAR & WAVESPRING KIT	050904SP	
16	1	WAVESPRING	150704SP	
17	2	SIDE GEAR THRUST WASHER	SEE NOTE	3
18	2	SHORT CROSS SHAFT	060403SP	
19	4	PINION GEAR	SEE NOTE	2
20	4	PINION THRUST WASHER	SEE NOTE	3
21	1	DIFFERENTIAL CASE	012206SP	
*	1	BULKHEAD FITTING KIT (BANJO TYPE)	170114	4
*	1	AIR LINE (6mm DIA X 6m LONG)	170314	4
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH	180209SP	
*	1	SWITCH COVER (FRONT)	180210SP	
*	1	SWITCH COVER (REAR)	180211SP	
*	1	CABLE TIE (PK OF 25)	180305	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	2102119	

NOTES

- 1 For replacement O-rings use only BS132 Viton 75.
- 2 Available only as complete 6 gear set #728H091
- 3 Available only as complete thrust washer kit #730H01
- 4 All diffs produced before serial #17070001 came with 5mm air connection system. For information contact ARB.
- For the 35 spline Ford 9" refer to RD99 (Section 2.99).
- Refer to seal housing set-up tech note (Section 5.2).



^{*} Not illustrated in exploded view





RD119

Ford 9",31 SPL

PARTICIPATION OF THE PROPERTY OF THE PROPERTY

SPECIFICATIONS

Axle Spline 31 tooth, Ø33.5mm [1.32"]

Ratio Supported A

Ring Gear ID 127.0mm [5.00"] Ring Gear OD 229mm [9"]

Ring Gear Bolts 10 bolts on Ø152mm [6.00"]

Ring Gear Torque 95Nm [70 ft-lb]

OEM Backlash 0.25-0.41mm [0.010-0.016"]

Non-OEM Backlash 0.18-0.25mm [0.007-0.010"]

Bearing Cap Torque 81Nm [60 ft-lb]