


Page 1 of 6 **99-0704** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/26/2014

		<u> </u>	PRODUC	CT & COM	Y <u>ANY</u>	<u>IDE</u>	<u>NTIF</u>	<u>ICA</u>	ПО	<u>N</u>				
.1	Product Name:	K&NA	IR FILTE	R SEALING	G GRE	ASE	=							
.2	Chemical Name:		nts listed in se											
.3	Synonyms:	K & N Air Filt	er Sealing Gre	ease, Sodium Gr	ease #2									
4	Trade Names:		er Sealing Gre											
5	Product Use:	Automotive L												
6	Distributor's Name:	K&N Enginee	ering, Inc.											
7	Distributor's Address:	P.O. Box 132	29, Riverside,	CA 92502-1329	USA									
8	Emergency Phone:	CHEMTRE	CHEMTREC +1 (800) 424-9300 / +1 (703) 527-3887 (CCN 632715)											
.9	Business Phone / Fax:		3-3333 / +1 (9			, -		,			,			
			2 LI	AZARDS I	DENT	IEIC	A TIC	\NI						
1	Hazard Identification:	This was done		as a HAZARDO						NOED	0110	0000		
		according to DANGER! N Classification Hazard State Precautionar SWALLOWE P305+P351+ contact lense	the classificating the classificating the classification of the cl	on criteria of NC LIF SWALLOV 004 – May be fat (P): P280 – We ly call a POISO N EYES: Rinse and easy to do. iner to an approv	HSC:108  IED AND  al if swalled ar protect  N CENTE cautious  Continu	88 (2004) ENTE  owed a ctive gla ER/doct ly with e rinsir	4) and RS All and ent oves/e tor. P water ng. F	ADG (RWAY) ers air eye pro 331 – for s 2405 –	Code ( 'S.  ways.  otectio  Do N  everal  Store	n. P30 OT incominute locke	ontendia. 01+P3 duce votes. d up.	310 – romitin Remov P501	F g. re	
2	Effects of Exposure:	Ingestion: Eyes: Skin: Inhalation:	May cause tr This product allergic skin r No significan	swallowed, may of ansient mild-eyed can cause mild eactions (e.g., rate t adverse healt liquid into the lui	irritation , transier ashes, we n effects	with sh nt skin elts, der are ex	ort-ter irritation matitis spected	m conton with s) upor	tact. h shor h prolo ccur u	t-term nged c pon sł	or repe nort-te	ated e	xposui	re.
.3	Symptoms of Overexposure:	may cause re	Aspiration of liquid into the lungs can cause severe lung damage or death.  Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure.											
4	Acute Health Effects:				fected are	eas.								
.5	Chronic Health Effects:	characterized	Moderate irritation to eyes and skin near affected areas.  Contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.											
.6	Target Organs:	Eyes, skin &	respiratory sy	stem.										
		3. CC	DMPOSII	ION & INC	KEDI	ENI	INF	OKI						
						AC	CILI		NOHSC	SURE LI	IMITS IN	AIR (m OSHA	g/m³)	1
							om .		ррт	•		ppm		{
								ES-	ES-	ES-				1
	ICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY		64742-52-5	NA	265-155-0	≤ 75	5	NA	NF	NF	NF	5	NA	NA	MIST
/DR	THENIC	Asp. Tox.1; H	1304											



SDS Revision: 2.0

Page 2 of 6 **99-0704** 

SDS Revision Date: 12/26/2014

4. FIRST AID MEASURES 4 1 First Aid: DO NOT INDUCE VOMITING. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Ingestion: Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, Eyes: holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek Skin: prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek Inhalation: immediate medical attention. If breathing stops, perform artificial respiration. 4.2 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 1 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES This material can burn but will not readily ignite. This material will release vapors when heated Fire & Explosion Hazards above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, phosphorus, zinc and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released. Extinguishing Methods: 5.2 Dry chemical, foam, carbon dioxide, and water fog. 5.3 Firefighting Procedures: Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Use normal hygiene practices. Avoid breathing vapors. Avoid direct skin contact. Wash hands thoroughly after using this product and before eating, drinking, or smoking. 7.2 Storage & Handling: Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Maximum Recommended Shelf-Life: 60 months. 7.3 Special Precautions: Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.



Page 3 of 6 **99-0704** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/26/2014

the recommended rmal temperatures			
> 5.0 (air = 1) 0.90 g/cm³ @ 15.°C (60 °F)			
Insoluble NA			
> 343 °C (650 °F)			
NA ND			
VEO			
YES			
or the components cument.			
_			
_			



Page 4 of 6 **99-0704** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.0 SDS Revision Date: 12/26/2014 11. TOXICOLOGICAL INFORMATION - cont'd 11.7 Irritancy of Product: See section 2.3 11.8 Biological Exposure Indices: ΝE 11 9 Physician Recommendations: Treat symptomatically. The viscosity range of the product(s) represented by this MSDS is greater than 400 SUS at 100°F. Accordingly, upon ingestion there is a low risk of aspiration. Careful gastric lavage or emesis may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl. Effects on Plants & Animals An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products 12.3 Effects on Aquatic Life: Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway can result in a loss of marine life or create an anaerobic environment. This material contains phosphorus which is a controlled element for disposal in effluent waters in most sections of North America. Phosphorus is known to enhance the formation of algae. Severe algae growth can reduce oxygen content in the water possibly below levels necessary to support marine life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Dispose of in accordance with federal & provincial hazardous waste laws. 13.2 Special Considerations If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local ordinance. 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED NOT REGULATED 14.2 IATA (AIR): 14.3 IMDG (OCN): **NOT REGULATED** TDGR (Canadian GND): NOT REGULATED 14 4 14.5 ADR/RID (EU): NOT REGULATED 14.6 SCT (MEXICO): **NOT REGULATED** ADGR (AUS): 14.7 **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, section 313 reporting requirements. Requirements SARA Threshold Planning 15.2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 15.5 Other Federal Requirements: This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects) 15.7 State Regulatory Information: Distillates (Petroleum), Hydrotreated Heavy Napthenic is listed on one or more of the following state criteria list: California Right-To Know (CA), Florida Toxic Substance List (FL), Minnesota Hazardous Substance List (MN), New Jersey Right-to-know List (NJ), Pennsylvania Hazardous Substance List (PA), Rhode Island Hazardous Substance List (RI), and Massachusetts Right-to-know List (MA). No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).



Page 5 of 6 **99-0704** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/26/2014

		15. REGULATORY INI	FORMATION – cont'd		
15.8	Other Requirements:	Distillates (Petroleum), Hydrotreated Heavy Harmful: may cause lung damage if swallov obtain special instructions before use. In casimmediately (show the label where possible).  Residual Oils, Petroleum, Solvent-Refined: cause lung damage if swallowed. Safety P	Not listed in Annex I of EU Directive 67/548/EEC:  Napthenic: Harmful (Xn). Risk Phrases (R): 65 – wed. Safety Phrases (S): 53-45 – Avoid exposure – the of accident or if you feel unwell seek medical advice Harmful (Xn). Risk Phrases (R): 65 – Harmful: may thrases (S): 53-45 – Avoid exposure – obtain special or if you feel unwell seek medical advice immediately		
		16. OTHER IN	FORMATION		
16.1	Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  Wear protective gloves/eye protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Store locked up. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN.			
16.2	Terms & Definitions:	See next page of this Safety Data Sheet.			
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's and K&N Engineering, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.			
16.4	Prepared for:	K&N Engineering, Inc. P.O. Box 1329 Riverside, CA 92502-1329 USA Tel: +1 (800) 858-3333 Fax: +1 (951) 826-4001 E-Mail: tech@knfilters.com http://www.knfilters.com	THE WORLD'S BEST AIR FILTER		
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate*  Dangerous Goods Training & Consulting		



Page 6 of 6 99-0704

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.0

SDS Revision Date: 12/26/2014

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
C Ceiling Limit	
IDLH Immediately Dangerous to Life and Health	
OSHA U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit	
TLV Threshold Limit Value	

#### FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard	
1	1 Slight Hazard	
2 Moderate Hazard		
3	Severe Hazard	
4	Extreme Hazard	



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		型	
D		型	
E			
F		西	





Splash Goggles



**Full Face Respirator** 

Synthetic Apron

Dust & Vapor Half-Mask Respirator

Face Shield & Protective Eyewear





Full Face

ð Airline Hood/Mask or SCBA

#### OTHER STANDARD ABBREVIATIONS:


ML	Maximum Limit
NA	Not Available
ND Not Determined	
NE Not Established	
NF Not Found	
NR No Results	
SCBA Self-Contained Breathing Apparatus	

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition   Minimum temperature required to initiate combustion in air with					
Temperature	source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will				
	explode or ignite in the presence of an ignition source				

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive
IREFUIL	Radioactive



#### TOXICOLOGICAL INFORMATION:

Lethal Dose (solids & liquids) which kills 50% of the exposed animals
S
Lethal concentration (gases) which kills 50% of the exposed animal
Concentration expressed in parts of material per million parts
Lowest dose to cause a symptom
Lowest concentration to cause a symptom
Lowest dose (or concentration) to cause lethal or toxic effects
International Agency for Research on Cancer
National Toxicology Program
Registry of Toxic Effects of Chemical Substances
Bioconcentration Factor
Median threshold limit
Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(*)</b>	<b>(2)</b>	<b>(3)</b>	$\odot$	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

		M	*			X	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			$\Diamond$		<b>\Partial</b>
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment

<u>CHEMTREC</u>	
n-Country Dial Numbers	

Local # Provided in Country

Toll Free in Country\*

**Greeting Language** 

AFRICA							
CHEMTREC South Africa*		0-800-983-611	English				

SOUTH AMERICA							
CHEMTREC Argentina (Buenos Aires)	+(54)-1159839431		Latin American Spanish				
CHEMTREC Brazil (Rio De Janeiro)	+(55)-2139581449		Portuguese				
CHEMTREC Chile (Santiago)	+(56)-225814934		Latin American Spanish				
CHEMTREC Colombia *		01800-710-2151	Latin American Spanish				
CHEMTREC Mexico*		01-800-681-9531	Latin American Spanish				
CHEMTREC Peru (Lima)	+(51)-17071295		Latin American Spanish				

ASIA							
CHEMTREC China*	4001-204937		Mandarin				
CHEMTREC Hong Kong (Hong Kong)*		800-968-793	Cantonese				
CHEMTREC India *		000-800-100-7141	Hindi				
CHEMTREC Indonesia*		001-803-017-9114	Indonesian				
CHEMTREC Japan (Tokyo)	+(81)-345209637		Japanese				
CHEMTREC Malaysia *		1-800-815-308	Malay				
CHEMTREC Philippines *		1-800-1-116-1020	Tagalog				
CHEMTREC Philippines (Manila)	+(63) 632-395-3308		Tagalog				
CHEMTREC Singapore*		800-101-2201	English and Mandarin				
<b>CHEMTREC Singapore</b>	+(65)-31581349		English and Mandarin				
<b>CHEMTREC South Korea*</b>		00-308-13-2549	Korean				
CHEMTREC Taiwan*		00801-14-8954	Mandarin				
CHEMTREC Thailand *		001-800-13-203- 9987	Thai				

AUSTRALASIA							
CHEMTREC Australia (Sydney)	+(61)-290372994		English				
CHEMTREC New Zealand (Auckland)*	+(64)-98010034		English				

	EUROPE		
CHEMTREC Belgium (Brussels)	+(32)-28083237		French and Flemish
CHEMTREC Czech Republic (Prague)	+(420)-228880039		Czech
CHEMTREC Denmark	+(45)-69918573		Danish
CHEMTREC France	+(33)-975181407		French
CHEMTREC Germany *		0800-181-7059	German
<b>CHEMTREC Hungary (Budapest)</b>	+(36)-18088425		Hungarian
CHEMTREC Italy *		800-789-767	Italian
CHEMTREC Italy (Milan)	+(39)-0245557031		Italian
CHEMTREC Netherlands	+(31)-858880596		Dutch
<b>CHEMTREC Poland (Warsaw)</b>	+(48)-223988029		Polish
CHEMTREC Portugal	+(351)-308801773		Portuguese
CHEMTREC Russia*		8-800-100-6346	Russian
CHEMTREC Slovakia (Bratislava)	+(421)-233057972		Slovak
CHEMTREC Spain*		900-868538	European Spanish
CHEMTREC Sweden (Stockholm)	+(46)-852503403		Swedish
CHEMTREC Switzerland (Zurich)	+(41)-435016715		Swiss German, French and Italian
CHEMTREC UK (London)	+(44)-870-8200418		English

MIDDLE EAST							
CHEMTREC Bahrain (Bahrain)	+(973)-16199372		Arabic				
CHEMTREC Israel (Tel Aviv)	+(972)-37630639		Hebrew				

\*Phone numbers for countries marked with an asterisk must be dialed within the country